
NOVO-GLOSS LITET

ACCURATE GLOSS MEASUREMENT MADE SIMPLE



Fast measurement with statistical analysis

One touch calibration with auto-verification





NOVO-GLOSS LITE™



FEATURES

AVAILABLE FORMATS

45°

Speciality finishes such as ceramics, textiles and anodised aluminium

CONTINUOUS READ

Assess gloss variations on a large surface in seconds

FLEXIBLE CALIBRATION

Calibrate on a standard that matches your sample for improved gloss control. Additional standards available from matt to mirror finish

STATISTICAL ANALYSIS

Automatic calculation of batch statistics

DOWNLOAD TO PC

Download your results to Novo-Soft for further analysis, reporting and storage

FXTRAS

FREE EXTENDED WARRANTY

Register for a two year comprehensive guarantee

FREE LIGHT SOURCE WARRANTY

Guaranteed for the life of the instrument

UKAS CALIBRATION

Instruments and calibration tiles are available with ISO 17025 certification

CALIBRATION AND SERVICE

Fast and economic service via our global network of accredited calibration and service centres

LOCAL AGENT

ACCESSORIES

BAM traceable calibration standard
Calibration tile cleaning kit
Quick-start guide
Data cable
Protective instrument case
Novo-Soft™ QA software CD
Full instruction manual in PDF format
Screwdriver

POWER OPTIONS:

Battery operated - 5 x AAA high power batteries



SPECIFICATIONS

Resolution 0.1GU
Repeatability 0.2%
Reproduceability 0.5%

Battery life 15,000+ readings

Languages EN, FR, D, NL, ESP, IT, TR

CONFORMITY

Standards:

ASTM C346 ASTM D2457 JIS 8741 ISO 7668





Certificate no: FM 29

